



#### Efficient

- Maximum efficiency of 98 %

#### Safe and Reliable

- Integrated web server for system management and monitoring

#### Flexible

- Greater versatility thanks to multistring technology

#### Easy-to-Use

- Innovative installation concept
- Ergonomic design and low weight

## FLX PRO 15 / FLX PRO 17

Three-phase inverters for small to medium-sized PV systems

The new line of three-phase inverters is the ideal solution for small to medium-sized PV systems. The inverters feature easy installation, high yields, simple commissioning and operation, integrated power management and excellent flexibility in PV system design.

The new, simplified installation concept offers exceptional ergonomics and unrestricted access to the installation area. Weighing no more than 39 kilograms, the inverters are very easy to handle and install.

# FLX PRO 15 / FLX PRO 17

Provisional Technical Data, 06/2014	FLX Pro 15	FLX Pro 17
<b>Alternating Voltage (AC)</b>		
Nominal apparent power	15 kVA	17 kVA
Nominal active power	15 kW	17 kW
Reactive power range	0 to 9.0 kVAr	0 to 10.2 kVAr
Nominal AC voltage range	3P+N+PE to 230/400 V (+/- 20 %)	
Nominal AC current	3×21.7 A	3×24.7 A
Max. AC current	3×22.6 A	3×25.6 A
AC total harmonic distortion (THD %)	<2 %	<2 %
Power factor—standard	>0.99 at nominal power	
Power factor—regulated	0.8 overexcited ... 0.8 underexcited	
Standby consumption	2.7 W	
Nominal power frequency (frequency range)	50 Hz (+/- 5 Hz)	
<b>Direct Current (DC)</b>		
Max. PV power per MPPT	8 kW	
PV nominal power, total	15.5 kW	17.6 kW
Nominal DC voltage	715 V	
Active MPPT voltage range / MPPT voltage range during rated operation	220/430 to 800 V	220/485 to 800 V
Max. DC voltage	1000 V	
System start-up voltage (DC)	250 V	
System shutdown voltage (DC)	220 V	
Max. DC MPPT current	12.0 A per input	
Max. DC short-circuit current	13.5 A per input	
MPP trackers/DC inputs	3 / 3 (SUNCLIX)	
<b>Efficiency</b>		
Max. efficiency	98.0 %	98.0 %
EU efficiency at nominal DC voltage	97.4 %	97.4 %
MPPT efficiency, static	99.9 %	
<b>Enclosure</b>		
Dimensions (W / H / D) / including packaging	667 × 500 × 233 mm / 774 × 570 × 356 mm	
Weight	39 kg	
Protection class	IP 65	
Noise emissions	55 db(A)	
Operating temperature range	-25 °C to +60 °C (possible power derating above +45 °C)	
Relative humidity	95 % (non-condensing)	
<b>Other</b>		
Active power	Fixed threshold, setpoint curves, remote control	
Reactive power	Constant, setpoint curves, remote control	
Interfaces	Ethernet, RS 485	
Options	GSM modem, sensor interface, power management	
Cooling concept	Fan	
<b>Safety</b>		
Certifications and approvals	See www.SMA-Solar.com	
Electrical safety	IEC 62109-1/IEC 62109-2 (Class I, grounded - Communication part Class II, PELV)	
Functional safety	Islanding detection/grid failure—three-phase monitoring Active frequency shifting and frequency change rate, Voltage and frequency monitoring, DC feed-in monitoring, insulation resistance monitoring Residual-current monitoring unit (RCMU)—Type B monitoring	
Ordering code	139F2105	139F2106